



New!

Weld Spatter Resistant Hose



SPATTER PVC/Polyurethane alloy hose tubing was developed by taking 95A durometer polyurethane inner tubing and jacketing it with a specially formulated flame retardant cover. The jacket prevents the hose from burn holes when in accidental contact with Weld Spatter. Outer cover features: strong insulating properties, resistant to oils, grease, aqueous solutions, ozone, heat aging and ultraviolet light.

Features:

- Highly abrasion-resistant alloy jacket.
- Smooth, non-marking pin-pricked cover.
- Good flexibility over a wide temperature range.
- Lighter weight than rubber.
- Good fitting retention at elevated temperatures.
- 3 to 1 safety (burst) factor

Applications:

- Transfer of air and water in welding and machine shops.
- Ideal for rugged & High Temp environments.
- Lubrication / air drop lines
- Robotic and pneumatic air lines.
- Automotive assembly line air hoses.
- For Temperature ranges from:
-40° F to +165° F

Re-Coil SPATTER Hose cpld 1/4" mpt swivels & spring guards. (GREY cover)

P/N	Description	W.P@75°F	Wt.ea
15026110	3/16"x15'	140 PSI	1.2#
15026120	1/4"x25'	140 PSI	2.3#

SPATTER Hose Assemblies: 5/16" I.D. cpld-mpt swivels & spring guards. (GREY cover)

P/N	Description	W.P@75°F	Bend Radius	Wt.ea
15026320	25'x1/4" mpt	140 PSI	1-1/8"	2.6#
15026325	50'x1/4" mpt	140 PSI	1-1/8"	5.0#
15026322	25'x3/8" mpt	140 PSI	1-1/8"	2.8#
15026327	50'x3/8" mpt	140 PSI	1-1/8"	5.3#

APACHE
HOSE & BELTING CO., INC.

Customer Service & National Sales 800.553.5455

www.apachehb.com